



RZ6.2

- new 6,5" 2-way speaker kit with wide-band tweeter

Reference series RZ6.2 is a brand new 16,5cm (6,5") 2-way component kit with a separate 50 mm / 2" wide band tweeter.

Install the tweeter on the dashboard, A-pillar or recessed in the door.

The bass driver has a paper cone with dual rubber edge and a 100 mm powerful magnet that guarantees a good bass control. Grilles are included.

Filter boxes with only the best components!



Technical data RZ6.2 woofer

Art.number	10-23161
Impedance	4 ohm
Nom. power handling (RMS)	100 Watt, 150 Watt max
Cone material	Pressed paper
Woofer size	6,5"(16,5 cm)
Magnet size	100 mm/4"
Sensitivity	85 dB
Mounting depth	70 mm/2,76"
Mounting hole	145 mm / 5,7"
Fs / Qts / Vas	64 Hz / 0,78 / 6,3 litres

Technical data RC50 wide band tweeter

Art.no. for driver	8-23050
Impedance	4 ohm
Size	50 mm / 2"
Nom. power handling (RMS)	50 Watt, 80 Watt max
Fs	155 Hz
Frequency response	500 Hz - 22 kHz
Rec. freq. use	1500 kHz - 22 kHz
Sensitivity	83,2 dB
Magnet diameter	32 mm / 1,26"
Outer diameter	84 mm / 3,3"
Mounting depth	37 mm / 1,46" (recessed install)
Mounting hole	65 mm / 2,56" (recessed install)
Cone material	Fibre glass

- We recommend installation in a closed box 0,2 - 1 litres

A low x-over point requires a larger box volume, a higher x-over point accepts a smaller box.

- Installation on axis is strongly recommended for a good result.

- Recommended x-over frequency for active crossover use is 1500 Hz or higher, use 12 dB slope.

- Connect with a good amplifier like DLS CC series or better.

DLS Sweden
www.dls.se
 E-mail. info@dls.se